

NEW!

Features, Performance, and **Travel Ready**



4-wheel

GO-GO[®]
SPORT



Easy Drive Tiller

The **Go-Go[®] Sport** delivers high-performance and convenience on the go. With a 147 kg (325 lb.) weight capacity, a charger port in the tiller, standard front LED lighting and a maximum speed up to 7.56 km/h (4.7 mph), the Go-Go[®] Sport is feature rich and travel ready.

PRIDE[®] MOBILITY SCOOTERS
LIVE YOUR BEST[®]



**FIRST
CHOICE
MOBILITY**

09 236 4233
027 424 6423 / 027 4 CHOICE
firstcmobility@gmail.com
www.firstchoicemobility.co.nz





Specifications 4W:SC74

Weight Capacity	147 kg (325 lbs.)
Maximum Speed ¹	Up to 7.56 km/h (4.7 mph)
Ground Clearance ²	3.8 cm (1.5") at motor
Turning Radius	128.3 cm (50.5")
Overall Length ²	109.2 cm (43")
Overall Width ²	54 cm (21.25")
Front Tyres	7.6 x 22.9 cm (3" x 9") solid
Rear Tyres	7.6 x 22.9 cm (3" x 9") solid
Range Per Charge ^{1,4}	Up to 19.3 km (12 miles)
Total Weight Without Batteries	44 kg (100 lbs.)
Heaviest Piece When Disassembled	20 kg (44 lbs.) (front section)
Standard Seating	Type: Foldable, compact, vinyl-covered, molded plastic Weight: 10 kg (23 lbs.) Material: Black Vinyl Dimensions: Width: 43.18 cm (17") Depth: 43.18 cm (17")
Motor Output	24-volt DC motor, sealed transaxle
Brakes	Regenerative and electromechanical
Battery Requirements ^{3,5}	(2) 12V deep-cycle (standard) Size: (2) 18 AH, 6.4 kg (14 lbs.) each Weight: 12.4 kg (27.4 lbs.) per battery pack
Battery Charger	Off-board, 2 amp
Colours	2 sets with every scooter!  

Red Blue

Features

- Charger port on tiller
- Convenient dual voltage charger can charge battery pack on-board or off-board
- Deck basket for additional storage
- Feather-touch disassembly permits simple frame separation with only one hand and easily disassembles into five super lightweight pieces for convenient transport and storage
- Front frame-mounted seat post offers maximum stability
- Front tiller-mounted basket
- Includes two sets of easily changeable, red and blue coloured panels
- Long-lasting, high-intensity, front LED headlight offers optimal pathway illumination
- Microprocessor-based controller offers optimal power management and added safety features
- Pride's exclusive black, non-scutting tyres

Accessories

- Pride® rear bag (includes crutch/walking stick holder)
- Walker holder (must have Pride® rear bag to attach)
- Oxygen tank holder (must have Pride® rear bag to attach)
- Saddlebag
- Mobile phone holder
- Cup holder
- Flag
- Rearview mirror

¹ Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tire condition. These specifications can be subject to a variance of (+/- 10%).

² Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³ AGM or gel cell type required.

⁴ Tested in accordance with ANSI/RESNA, WC Vol2, section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.

⁵ Battery weight may vary based on manufacturer.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on accessory selections.



09 236 4233
027 424 6423 / 027 4 CHOICE
firstcmobility@gmail.com
www.firstchoicemobility.co.nz

